

DH351

High resolution presentations



- **Lights on viewing – 3600 ANSI lumens**
- **Easy connectivity – HDMI, USB power**
- **Portable and lightweight**
- **Built-in audio**



Project bright Full HD 1080p images with the DH351. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts ease of use with its single HDMI connection and built-in speaker. You can even use the USB power to connect and power HDMI dongles such as the Google Chromecast.

Specifications

EAN: 5055387663701, Colour: Black

Display/image	
Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	3.600 lumens
Contrast ratio	22.000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Uniformity	80%
Screen size	0.71m ~ 7.65m (28" ~ 301") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.47:1 ~ 1.62:1
Projection distance (m)	1m - 9.8m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.59mm~17.14mm/0.614"~0.675"
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	5W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDcast Pro, WHD200
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	205W
Power consumption (max)	295W
Weight and dimensions	
Dimensions (W x D x H) mm	316 x 244 x 108
Gross weight	3.81 kg
Net weight	2.8 kg

