


# ZH400UST

Laser 1080p Ultra Short Throw Projector



© Samruh Creative Association

- **Bright Full HD 1080p laser projector - 4000 ANSI lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **30,000 hours maintenance-free laser light source**
- **Dust resistant – Independently tested, IP5X certification for total reliability**



The ZH400UST is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a low total cost of ownership.

Weighing only 5.6kg, this projector can be mounted just centimetres away from a wall or surface and can project an image size of over 100 inches (254cm).

Supporting 24/7 operation and versatile orientation, the ZH400UST is a flexible, powerful and bright ultra short throw projector which makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.

# Specifications

EAN: 5055387643307, Colour: White



|                                |                                     |
|--------------------------------|-------------------------------------|
| <b>Display/image</b>           |                                     |
| Display technology             | DLP™                                |
| Resolution                     | 1080p Full HD (1920x1080)           |
| Brightness                     | 4,000 lumens                        |
| Contrast ratio                 | 100,000:1                           |
| Native aspect ratio            | 16:9                                |
| Aspect ratio - compatible      | 4:3                                 |
| Keystone correction - vertical | +/-15°                              |
| Horizontal scan rate           | 15.3 ~ 91.1Khz                      |
| Vertical scan rate             | 24 ~ 85(120 for 3D)Hz               |
| Uniformity                     | 80%                                 |
| Screen size                    | 2.21m ~ 2.59m (87" ~ 102") diagonal |

|                   |              |
|-------------------|--------------|
| <b>Lamp info</b>  |              |
| Light source type | Laser        |
| LASER life        | 30,000 hours |

|                         |               |
|-------------------------|---------------|
| <b>Optical</b>          |               |
| Throw ratio             | 0.25:1        |
| Projection distance (m) | 0.45m - 0.59m |
| Zoom type               | Fixed         |
| Focal length (mm)       | 3.72mm/0.146" |
| Native offset           | 120%          |

|                     |  |
|---------------------|--|
| <b>Connectivity</b> |  |
| Connections         | <b>Inputs</b> 2 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 1 x Audio RCA L&R<br><b>Outputs</b> 1 x VGA shared with VGA2, 1 x Audio 3.5mm, 1 x USB-A power 2A<br><b>Control</b> 1 x RS232, 1 x RJ45, 1 x mini USB service, 1 x USB-A wireless |

|                          |   |
|--------------------------|---|
| <b>General</b>           |   |
| Noise level (typical)    | 30dB  |
| Noise level (max)        | 32dB  |
| PC compatibility         | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  |
| 2D compatibility         | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)   |
| 3D compatibility         | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D  |
| 3D                       |   |
| Security                 | Security bar, Kensington Lock, Password protected interface   |
| OSD / display languages  | 17 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional), Turkish |
| Operating conditions     | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%  |
| Remote control           | Yes   |
| Heat dissipation         | 890BTU/hour   |
| Speaker count            | 1   |
| Watts per speaker        | 10W   |
| In the box               | AC power cord<br>Remote control<br>2x AAA batteries<br>Basic user manual  |
| Optional wireless models | HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200, WUSB   |

|                   |     |
|-------------------|-----|
| <b>Networking</b> |     |
| LAN - control     | Yes |

|                             |                       |
|-----------------------------|-----------------------|
| <b>Power</b>                |                       |
| Power supply                | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W                  |
| Power consumption (min)     | 210W                  |
| Power consumption (max)     | 330W                  |

|                              |                 |
|------------------------------|-----------------|
| <b>Weight and dimensions</b> |                 |
| Dimensions (W x D x H) mm    | 382 x 310 x 124 |
| Gross weight                 | 8.46 kg         |
| Net weight                   | 7.19 kg         |

