

HD146XW

Big screen entertainment









- Ideal for daytime viewing 3600 lumens
- Amazing colour Bright vivid images
- Easy connectivity HDMI and USB power
- Built-in audio Ultimate convenience for an easy set-up



The Full HD 1080p HD146XW projector is ideal for watching live sport,

TV shows or movies any time of day. Convenient and easy to set up this
bright and versatile projector boasts Amazing colour technology delivering bright and vivid images. It also has low input latency – perfect
for games and fast-moving events that rely on rapid reactions.

Specifications

EAN: 5055387667105, Colour: White

Display/image
Display technology

DLP™

Resolution 1080p Full HD (1920x1080)

 Brightness
 3,600 lumens

 Contrast ratio
 25,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3

 Keystone correction - vertical
 +/-40°

 Uniformity
 80%

Screen size 0.71m ~ 7.65m (28" ~ 301") diagonal

Lamp info
Light source type
Lamp watts
240

Lamp life hours (up to) 4000 (Bright), 15000 (Dynamic), 10000 (Eco)

Optical Throw ratio

 Throw ratio
 1.47:1 ~ 1.62:1

 Projection distance (m)
 1m - 9.8m

 Zoom
 1.1

 Zoom type
 Manual

Focal length (mm) 21.86mm~24mm/0.614"~0.675"

Native offset 115%

Connectivity

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x Composite video, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D support + MHL

Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-

A power 1A Control 1 x RS232

______ General

Noise level (typical) 29dB Noise level (max) 31dB

 PC compatibility
 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

 2D compatibility
 NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.45MHz PAL b/D/G/F/I/MMN, 4,45MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D

 Security
 Security bar, Kensington Lock, Password protected interface

 OSD / display languages
 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified). Spanish Swedish Chinese (traditional)

Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Backlit home remote

Speaker count 1

Watts per speaker 2W

In the box AC power cord

Remote control 2x AAA batteries Basic user manual

Input lag16.00msOptional wireless modelsWHD200

Power

Power supply 100 ~ 240V, 50 ~ 60Hz

 Power consumption (standby)
 0.5W

 Power consumption (min)
 204W

 Power consumption (max)
 266W

Weight and dimensions

 Dimensions (W x D x H) mm
 298 x 230 x 96

 Gross weight
 3.31 kg

 Net weight
 2.82 kg





