

EH515T

Powerful performer



© Samruh Creative Association

- **Ultra bright Full HD 1080p projector – 5500 ANSI lumens**
- **Installation flexibility – 1.8x zoom**
- **Vertical and horizontal lens shift**
- **Four corner geometric projection**

This large venue projector produces Full HD quality images for an uncompromising level of detail. Designed for professional installation environments, the EH515T boasts a brightness of 5500 lumens and features multiple digital connection options, with two HDMI inputs, DisplayPort and HDBaseT™. For more complex installations, this projector is equipped with a large zoom range, lens shift and a built-in geometric adjustment feature - ideal for image stacking, uneven walls or where a projector placement is awkward and needs to be installed at an angle.



Specifications

Affichage/image	
Technologie d'affichage	DLP
Résolution native	1080p Full HD (1920x1080)
Luminosité ¹ (mode Lumineux)	5 500 lumens
Contraste	10 000:1
Affichage (natif)	16:10
Aspect ratio - compatible	4:3,16:9
Correction trapèze - horizontale	+/-30°
Correction trapèze - verticale	+/-30°
Correction trapèze automatique verticale	Oui
Nombre de couleurs (millions)	1073.4
Fréquence de balayage horizontal	15.375 ~ 91.146Khz
Taux de rafraîchissement vertical	24 ~ 85(120 for 3D)Hz
Uniformité	80%
Taille d'écran	0.69m ~ 7.62m (27.2" ~ 300") diagonale
Lampe (Infos)	
Source lumineuse	Lampe
Lampe watts	365
Durée de vie de la lampe (hrs)	3000 (Lumineux), 5000 (Eco+)
Optique	
Rapport de projection	1.2:1 ~ 2.16:1
Distance de projection (m)	1.3m - 8m
Zoom	1.8
Type de zoom	Manuel
Longueur de la focale (mm)	17.63 ~ 31.36
Lens shift	Vertical +25%, Horizontal +10%
Offset natif	105%
Connectivité	
Connectiques (Entrées/Sorties)	Entrées 1 x DisplayPort, 2 x VGA (YPbPr/RGB), 1 x HDMI 1.4a 3D support, 1 x HDMI 1.4a 3D support + MHL, 1 x Composite vidéo, 1 x S-Vidéo, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x RS232, 1 x USB-B souris/service Sorties 1 x Audio 3.5mm, 1 x Relais 12V, 1 x USB-A power 1.5A, 1 x 3D sync
Général	
Niveau sonore (type)	28db
Compatibilité PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilité 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilité 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Sécurité	Barre de sécurité, Encoche Kensington, Protection par mot de passe
OSD / Affichage des langues	25 Langues: Arabe, Tchèque, Norvégien/Danois, Néerlandais, Anglais, Farsi, Finnois, Français, Allemand, Grec, Hongrois, Indonésien, Italien, Japonais, Norvégien, Polonais, Portugais, Roumain, Russe, Chinois Simplifié, Espagnol, Suédois, Chinois Traditionnel, Turque, Vietnamien
Fonctionnement 24/7	Oui
Conditions de fonctionnement	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Télécommande	Télécommande rétro-éclairée ProAV
Nombre de Haut-parleurs	2
Haut-parleur (Watts)	10W
Contenu de la boîte	AC power cord Remote control, 2x AAA batteries Basic user manual
Modèles sans fil en option	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Réseau	
LAN - Contrôle	Oui
Puissance	
Alimentation	100V ~ 240V ± 10%, 50-60Hz
Consommation énergétique (veille)	0.5W
Consommation énergétique (min)	340W
Consommation énergétique (max)	425W
Poids et dimensions	
Poids Net	5.9kg
Dimensions (LxPxH)	424 x 344 x 160mm



Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 28032020122219