

ull HD

1080p







- Ideal for daytime viewing 3600 lumens
- Amazing colour Bright vivid images
- Easy connectivity HDMI and USB power
- Built-in audio Ultimate convenience for an easy set-up



The Full HD 1080p HD146XW projector is ideal for watching live sport, TV shows or movies any time of day. Convenient and easy to set up this

bright and versatile projector boasts Amazing colour technology delivering bright and vivid images. It also has low input latency – perfect for games and fast-moving events that rely on rapid reactions.

Specifications

| - | |
|--|---|
| EAN: 5055387667105, Colour: V | Vhite |
| Display/image | |
| Display technology | |
| Resolution | 1080p Full HD (1920x1080) |
| Brightness | 3,600 lumens |
| Contrast ratio | 25,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3 |
| Keystone correction - vertical | +/-40° |
| Uniformity | 80% |
| Screen size | 0.71m ~ 7.65m (28" ~ 301") diagonal |
| Lamp info | |
| Light source type | Lamp |
| Lamp watts | 240 |
| Lamp life hours (up to) | 4000 (Bright), 15000 (Dynamic), 10000 (Eco) |
| Optical | |
| Throw ratio | 1.47:1 ~ 1.62:1 |
| Projection distance (m) | 1m - 9.8m |
| Zoom | 1.1 |
| Zoom type | Manual |
| Focal length (mm) | 21.86mm~24mm/0.614"~0.675" |
| Native offset | 115% |
| | I I ∪ 70 |
| Connectivity | |
| Connections | Inputs 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x Composite |
| | video, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D support + MHL |
| | Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB- |
| | A power 1A |
| | Control 1 x RS232 |
| General | |
| Noise level (typical) | 29dB |
| Noise level (max) | 31dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz |
| | SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, |
| | 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: |
| | 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, |
| | Finnish, French, German, Greek, Hungarian, Indonesian, Italian |
| | Japanese, Norwegian, Polish, Portuguese, Romanian, Russian |
| | Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| Operating conditions | |
| Operating conditions | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% |
| Remote control | Backlit home remote |
| | 1 |
| Speaker count | |
| Watts per speaker | 2W |
| In the box | AC power cord |
| | Remote control 2x AAA batteries |
| | Basic user manual |
| Input lag | 16.00ms |
| Optional wireless models | WHD200 |
| Power | |
| | 100 ~ 240V, 50 ~ 60Hz |
| Power supply | |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 204W |
| | 266W |
| Power consumption (max) | 20011 |
| Power consumption (max) Weight and dimensions | 20000 |
| Power consumption (max) | 298 x 230 x 96 |
| Power consumption (max) Weight and dimensions | |





Copyright © 2022, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 02112022083050